



can to know more

## **Corporate Office**

SG Centre, 37C, Block A, Sector 132, Noida, Uttar Pradesh 201304, India T: +91 - 120 6918000 F: +91-120 4041444

Stay connected. Stay updated.

**IF** in ⊗ **ID** Ø / APL APOLLO COATED STEEL OFFICIAL TOLL FREE: 1800-102-3737

Website: www.aplapollocoatedsteel.com | email: coatedsteelmarketing@aplapollo.com








# RADIANT RESILIENCE

FOR UNMATCHED SHINE AND STRENGTH





## **CONTENTS**

ADOUL APL APOIIO	
Sustainability Is At The Core Of APL Apollo	3
Dur Plant	5
About Glitz	7
he Glitz Advantages	9
Product characteristics	11
Applications	13

## **ABOUT APL APOLLO**

Welcome to APL APOLLO, where innovation, excellence, and reliability converge to redefine the steel industry. As a premier manufacturer and supplier of high-quality steel products, we take pride in our commitment to pushing boundaries and setting new standards in the industry.

APL Apollo Tubes Limited is the largest producer of Structural Steel Tubes in India.

### Our Legacy of Excellence:

With a legacy spanning over a decade, APL APOLLO has emerged as a global leader in the production of structural steel tubes. Our unwavering dedication to quality and customer satisfaction has propelled us to the forefront of the industry, earning us recognition as one of the largest players worldwide.

### **Innovative Capacity Investment:**

We believe in investing in the future. Through consistent investment in our manufacturing capacities, we have positioned ourselves as pioneers in the industry. Our strategic approach to capacity creation ensures a balanced manufacturing infrastructure across regions, enabling us to meet demand with precision and efficiency.

### **Pioneering Technology Adoption:**

At APL APOLLO, innovation is ingrained in our DNA. For the past two decades, we have been at the forefront of bringing cutting-edge technology to India's shores. From groundbreaking manufacturing processes to state-of-the-art machinery, we continuously push boundaries to create new products and markets.

### **Expansive Product Portfolio:**

Our commitment to innovation is reflected in our expansive product portfolio, comprising over 2,000 SKUs. From structural tubes to hollow sections, pre-galvanized tubes to precision tubes, we offer a diverse range of products that cater to a multitude of applications and sectors.

30 Countries Across the Globe

Steel Products

Manufacturing Units



### **Robust Distribution Network:**

We understand the importance of accessibility. That's why we have developed the largest and most expansive distribution network in the industry. Supported by robust supply chain solutions, our multi-layer network ensures that our products are readily available across India.

## **Driving Trade Transformation:**

We are not content with just meeting benchmarks; we strive to set them. By providing innovative products, rapid delivery, and growth opportunities to our channel partners, we have revolutionized trade practices within the industry.

### A Commitment to Innovation:

Innovation is at the heart of everything we do. We remain steadfast in our commitment to developing innovative solutions that address evolving customer needs and deliver increased value. Our cutting-edge facility near Raipur is a testament to this commitment, where we manufacture value-added products that are firsts for the Indian markets.

## SUSTAINABILITY IS AT THE CORE OF APL APOLLO

Our environmental management is not a strategy but a philosophy embedded in the substrata of the enterprise, it allows us to reduce our carbon footprint and also inspires our customers meet their own environmental management aspiration.

### **PRODUCTS:**

We are the first and pioneering Company to innovate readymade Chaukhat, Fence, Plank, and Hand rails under Steel for Green concept which replaced conventional wood applications in building construction.

Our product saves approximately 250,000 trees every year.

### **ENERGY:**

Our total renewable energy stood at 49,618 MW, which is 38% of APL Apollo's total energy consumption. To achieve its near-term emissions reduction targets, APL Apollo plans to increase the use of renewable energy. At two of APL Apollo's plants (in Malur, Karnataka and Hosur, Tamil Nadu), over 85% of energy needs were met through renewable energy.

### **GREEN COVER:**

We have planted 5,000 plants on 3.1 acres of government-provided land in Gendupur Village, Sikandrabad, close to our AMPL (A25/Plot 22) and APL A19 manufacturing plants.
Furthermore, we have undertaken a large number of plantation activities in our plants at

APL Apollo Building Products Private Limited (ABPL). For the plantation of thick, natural mini-forests, we have adapted the Miyawaki technique pioneered by the Japanese botanist Akira Miyawaki. The method will result in ten times faster plant growth and a plantation that is 30 times denser than typical.

### **WATER:**

Over the years, we have persevered to optimise water consumption at our facilities by strengthening our shop-floor processes.

Our patient efforts have yielded heartening results. Over the last three years (FY20-FY23), our total water consumption declined by 9% YoY despite a 30% jump in production. Our two facilities at Murbad and Malur are Zero-Liquid Discharge certified. To rejuvenate the groundwater table, we have created rainwater harvesting pits of around 353 cubic meters.

Dow Jones
Sustainability Indices
In Collaboration with RobecoSAM 60



# **DJSI FY2023 SCORE**

# APL APOLLO TUBES STANDS AT 86

(IN THE PEER INDUSTRY COMPRISING OF GLOBAL COMPANIES)

SCORE REACHED A HIGH OF 40 POINTS, ABOVE THE INDUSTRY AVERAGE OF 24

IMPROVEMENT ACROSS AREAS



Social Dimension



Governance & Economic Dimension



Environmental Dimension

## **OUR PLANT**

The Raipur Facility: Driving Innovation and Sustainable Growth

## **Manufacturing Plant Overview:**

APL Apollo's manufacturing facility located at Simga, Raipur spans across a vast 600-acre landscape, our facility stands as a testament to our commitment to excellence in the manufacturing of steel tubes and building products.

With a current annual capacity of 1 million tons and additional expansion capabilities of 0.3 million tons, our facility is equipped to meet the growing demands of various industries.

## Our facility boasts a range of groundbreaking product innovations, including:



India's first 20mm HR Slitting Line



Introduction of 1000 x 1000mm Structure Tubes, a pioneering feat in India and globally.



Launch of India's first 500 x 500mm Structure Tube Section



Implementation of India's first Thicker Colour Coating Line, offering superior coating thickness ranging from 1.60mm to 2.50mm

## Our operations prioritize environmental sustainability, with features such as:

- A Zero Discharge Plant, ensuring minimal environmental impact.
- Implementation of an Acid Regeneration Plant, promoting eco-friendly practices.




## **ABOUT GLITZ**

Glitz is APL Apollo's tribute to the ever-changing pattern of steel demand. It is environmentally safe and economically advantageous. With Glitz, we have redefined quality and raised the bar of strength, durability, performance and versatility.

In the world of high GP thickness, we're offer Normal Spangle/Suppressed or Crushed Spangle Galvanised Plain (GP) steel in the country. Glitz stands out with unmatched surface finish and mechanical properties with capabilities to meet the stringent quality requirements of customers.

A high level of corrosion resistance, superior flatness, and an excellent surface suitable for painting are a few attributes that characterize our coated products. This product can be used in a wide variety of applications.


### **RUST UNDERCUTS SCRATCHED PAINT**



Paint on non-galvanised steel

This is what happens at a scratch on painted non-galvanised steel. The exposed steel corrodes and forms a pocket of rust. Because rust is much more voluminous than steel, the pocket swells. This lifts the paint film from the metal surface to form a blister. Both the corrosion pit and the blister continue to grow.

### ZINC PROTECTS BASE STEEL, EVEN WHEN SCRATCHED



Galvanised steel

This is what happens at a scratch on galvanised steel. The zinc coating sacrifices itself slowly by galvanic action to protect the base steel. This sacrificial action continues as long as any zinc remains in the immediate area. Bare galvanised steel and painted galvanised steel are the best answers to corrosion.



## THE GLITZ ADVANTAGE



Excellent Surface Finish & Flatness: The Galvanized steel coil's shiny and spangled appearance, elevates aesthetics and functionality with flawless finish and precise flatness.



Superior Paint Adhesion: Achieve long-lasting color and surface protection with the superior paint adhesion.



Uniform & Superior Zinc Adhesion: Uniform and superior zinc adhesion in Glitz prevents zinc peel-off & crazing (pebby surface) during fabrication, thereby ensuring end-product durability & finish. Uniform zinc coating is possible through Feed-Forward X-ray mechanism in Continuous Galvanising Line.



Consistent Thickness: Glitz comes in uniform and close tolerance of thickness which ensures higher yield in end applications – meaning more number of parts per kg compared to ordinary Galvanised products.

Thickness Tolerance*	
Thickness/Allowable Tolerance/Width	Width upto 750 mm
1.50mm to 2.00mm	± 0.04
2.01mm to 2.50mm	± 0.05
2.51mm to 2.80mm	± 0.06

\*On nominal thickness measured at 10 mm from the edge



Optimum Formability & Excellent Draw Ability: Glitz is made from steel substrate made through close control of chemical composition and having best mechanical properties – the key for forming applications.

Optimize manufacturing efficiency with the smooth airflow properties.



Eco-Friendly: Choose sustainability without compromising performance with our environmentally friendly steel solutions.



**Enhanced Corrosion Resistance:** Boost infrastructure longevity and reduce maintenance expenses with zinc-coated steel, effectively warding off corrosion for prolonged durability.

	Chromated		Thin Orga	anic Coated
Company	White Rust Resistance	Red Rust Resistance	White Rust Resistance	Red Rust Resistance
ABPL	100-120 hrs	500-700hrs	500-550hrs	800-900hrs
Others	60-100 hrs	400-600 hrs		

\*Based on 275 gsm coating as per ASTMB117 and post treatment of Thin Organic Coated

## **WELDABILITY**

Welding on Glitz is done almost by the same welding processes done for bare steel, but with minor changes in voltage, amperage, travel speed, etc. Common welding tips are Spot welding & GMAW welding

## **GLITZ COIL QUALITY TESTING**

Glitz, our premier product, prioritizes quality assurance above all else. The rigorous testing procedures, focusing on flexibility and coating adhesion, demonstrate our dedication to excellence. Bend tests, conducted meticulously according to material specifications, evaluate the zinc coating's adhesion. Additionally, impact and cupping tests are systematically performed on every product to ensure consistent and robust adhesion across our range. These stringent quality control measures reflect our commitment to delivering products of unmatched quality and durability.



## PRODUCT CHARACTERISTICS

Dimensions:

Thickness: 1.50 – 2.80 mm

Width: 100-750 mm

Inner dia: 508 mm

Outer dia: 1900 mm max

Weight: 15 tons max

**Grades:** G300 / G350 / G450

**Surface Condition:** Galvanized Normal Spangled/Suppressed or Crushed Spangle

Coating Mass: Galvanised: Z80/Z120/Z180/Z275 (total both sides)

**Post Treatment:** Chromated/Thin organic coated (CR+3/CR+6)

## **TECHNICAL SPECIFICATIONS**

Brand Name	Glitz
Product Name	Hot Dipped Galvanized Steel Sheets in Coil form
Reference Standard	IS 277
Thickness Range (TCT) mm	1.50 to 2.80
Width Range (mm)	100 to 750
Zinc Coating Grade (GSM)	Z 80 to Z 275

Properties of Steel Base (Other steel base possible on agreement)				
Element	Chemical Composition (% max)			
	GP300	GP350 Class-1	GP350 Class-2	GP450
Carbon (C)	0.25	0.25	0.25	0.2
Manganese (Mn)	1.35	1.5	1.5	1.35
Phosphorus (P)	0.05	0.05	0.05	0.04
Sulphur (S)	0.035	0.035	0.035	0.03
Aluminium (Al)	0.02-0.07	0.02-0.07	0.02-0.07	0.02-0.07

Available Dimension Range & Tolerances				
Base Metal T	hickness (mm)	Widt	th (mm)	
Thickness Range	Tolerances	Range	Tolerance	
1.50 - 2.80	± 0.06	100-750	+2/-0	
Surface Treatment	Chromic acid (ideally even coatings of 20 to 40 mg/m2 total on both sides) is normally applied to all galvanised material			
Video Jet Printing	APL APOLLO GLITZ/MPA/GSM/MM			
Spangle Type	Regular Spangle /Normal Spangle/Suppressed or Crushed Spangle			
Coated Surface	Bright Metallic Appearance			
Flexibility and Coating Adhesion	Bend tests as per IS 277			
Properties	Providing a barrier between the steel and the environment through galvanic protection			
Applications	Widely used in PEB, Structuratl Steel, Cladding, Purlin and Colour Coating			

Mechanical Property				
	Tensile Test		Bend Test (Mandrel Diameter 180°)	
Material Grade	YS (Mpa) Min	UTS (Mpa) Min	(%) El @ GL-50 mm*	Thickness t > 1.25 mm
YS 300	300	400	20	3t
YS 350 Class 1	350	420	13	3t
YS 350 Class 2	350	A STATE OF THE STA	13	4t
YS 450	450	480	9	4t

## **APPLICATIONS**















