



हिन्दुस्तान पेट्रोलियम कॉर्पोरेशन लिमिटेड

(भारत सरकार उपक्रम) रजिस्टर्ड ऑफिस : 17, जमशेदजी टाटा रोड, मुंबई - 400 020.

HINDUSTAN PETROLEUM CORPORATION LIMITED

(A GOVERNMENT OF INDIA ENTERPRISE) REGISTERED OFFICE : 17, JAMSHEDJI TATA ROAD, MUMBAI - 400 020.



8, शूरजी वल्लभदास मार्ग, पोस्ट बॉक्स नं. 155, मुंबई - 400 001. • दूरभाष : 022-2263 7000, ई-मेल : Mktghqo@hpcl.in
8, Shoorji Vallabhdas Marg, P. O. Box No. 155, Mumbai - 400 001. • Tel. : 022-2263 7000, E-mail : Mktghqo@hpcl.in

CIN No.: L23201MH1952GOI008858

RET/DHVA/RE-Roofing Sheet

Date: 8th December 2025

M/s. **APL APOLLO BUILDING PRODUCTS PVT LTD**
SG Centre
Noida Sector 132
Uttar Pradesh

Kind Attn: Rakesh Prasad, GM (Business Development & Marketing)

Sub: Enlistment of Manufacturers for supply of enlist manufacturers for CANOPY ROOF SHEET

Sir,

We are pleased to inform you that you have been enlisted, as one of the authorized vendors for supply of " **CANOPY ROOF SHEET** " to HPCL OR HPCL appointed Converters for Canopy works Based on technical evaluation, factory visit, sampling and subsequent test report of samples from NABL accredited laboratory for testing relevant BIS standards as defined under the specification. This approval for under the brand name "APL APOLLO" enlistment of material is factory specific, as per following details:

Name of Vendor : **M/s. APL APOLLO BUILDING PRODUCTS PVT LTD**

Brand : **'APL APOLLO'**

Approved for material : **CANOPY ROOF SHEET**

Details of manufacturing facility approved for supply of material

M/s. APL APOLLO BUILDING PRODUCTS PVT LTD
Village Ringini & Keshda,
Tehsil Simga, Baloda Dist ,
CHATTISGARH

The **CANOPY ROOF SHEET** is to be supplied from above approved factory only and strictly in compliance with technical specifications as mentioned in the tender documents. In case, if you desire to change or changes its manufacturing location, prior approval shall have to be taken from HPCL. The specifications of the roofing sheet is as given under :

(Signature)



1. Specifications of ROOFING CLIPPON:

DESCRIPTION => Supply and fixing Clippon Roofing System: Roofing base material should be of cold rolled steel of 0.55 mm thick and conform to ASTM:A 446 having yield stress of 275 MPA . The coating should be Aluminum and Zinc alloy comprising 55% Al, 43.5 Zinc & 1.5 % Silicon, as per ASTM :A 792. The coating mass should not be less than 150 Gms per SqM (total of both sides). For, bare galvalume, TCT should not be less than 0.55 mm. Sheets shall have approved side laps with top sheets facing away from the prevailing weather. Necessary profiled filler box should be provided at higher level of roof sheeting and at valley gutter to ensure water tightness in the profiled gaps . The fixing of roofing shall be done in such a manner that the roof is not drilled / punctured for fixing with the purlins .Refer to the approved makes given in the Attachment. Flashings, Cappings and trims: These shall be formed out of same substrates as that of the roofing sheets and shall be supplied in standard lengths of 2.5 M in the required shapes and girths and fixed by means of hex-head mechanically galvanized stitching screws. Silicon sealant non-hardening neutral cure type shall be applied at all laps to avoid water seepage.

2. Specifications of ROOFING TRACDEK HI RIB 100:

DESCRIPTION => Providing and installing roofing Ribbed roofing system manufactured with high strength steel grade of G550(550MPa) of ZINCALUME steel or approved equivalent bare Galvalume high tensile cold rolled steel as per ASTM 117 A792M /AS 1397 Coating class AZM 150 (minimum 150 gm/sqm Zinc-Aluminium alloy coating mass total of both sides),of Yield strength 550 Mpa Thickness of bare metal (BCT): 0.40mm ,Total coated thickness(TCT) : 0.45 mm .Approximate mass of roofing sheet shall be 4.17 Kg/sqm. Panels shall be of Min. 900 mm wide and Min. corrugation depth of 38 mm with varying lengths as per Site requirements Rate shall be including laying of sheets with approved fasteners and also all weather sealant tape as per Mfr's recommendations and also providing ribbed galvalume ridge pieces of the same class as of the matching corrugation profile of the roofing system as recommended by the Mfr.and , horizontal/vertical flashing near illuminated banding.

It is reiterated that you shall provide 20 Years warranty of free replacement for any manufacturing defects. Warranty certificate issued to the HPCL appointed converter shall be mentioning the HPCL PO No issued to the converter and also the name of the HPCL site (Name of retail outlet, Location, District, State). These certificates shall be hosted on Manufacturer's portal for verification by HPCL.

Signature



This enlistment shall remain valid as per the requirements of HPCL & further HPCL reserves the right to de-list any vendor from the approved make, based on not meeting the requisite quality standards at any point of time.

This letter is a mere confirmation of your enlistment under Approved makes list for **CANOPY ROOF SHEET** and does not entail any confirmed orders or commitment from HPCL

By a copy of this letter, we are informing all our Zonal/Regional Offices for inclusion in the approved makes list of " **CANOPY ROOF SHEET** ".

Thanking you and assuring you of our best co-operations at all times.

Yours truly,

D H V Anand

GM-RE, HQO

(For Hindustan Petroleum Corporation Limited)